



Instructions for cleaning and care

PU sealed flooring types

TAKIRON

Flooring type: *Takiron MT*

1. Preventive measures

Much of the ingress of dirt can be avoided by installing dirt traps in front of doorways and clean-off zones in entrance areas. This reduces the amount of cleaning work and prolongs the useful life of the floor covering. In order for them to continue performing their intended function for a long time, they must be regularly cleaned or replaced.

2. Cleaning of newly installed floors/Cleaning and stripping

Before it is used for the first time and during regular use, the floor must be subjected to thorough cleaning (in the case of newly installed floors)/cleaning and stripping operation at regular intervals. This removes installation or production related residues in the case of newly installed flooring and clears away layers of old care products and particularly stubborn dirt present on older floors.

For this purpose use *PU Cleaner* (for newly installed floors) resp. *Clean and Strip R* diluted with water in a ratio of between 1:5 and 1:10. In case of low levels of building dirt, the concentration should be reduced to correspond to the actual dirt level. Clean flooring types with a closed surface structure with a suitable mop (e.g. the *Quick-Step*) or using an automatic cleaning appliance with integrated water extraction function (e.g. the *Premium F2*). A suitable pressure cleaner appliance can be used in wet rooms and outside areas.

3. Routine Cleaning and Care

- 3.1 *Dust Removal:* Loose surface dust and dirt is removed by wiping over the floor with a slightly damp mop or with a powerful brush vacuum cleaner (e.g. *Carpetlife brush vacuum cleaner*)
- 3.2 *Manual Wet Cleaning:* For the removal of adherent soiling, dilute *PU Cleaner* in a ratio of 1:200 and clean the floor by applying the two-step damp mopping procedure. Treat those areas which have to be cleaned with disinfectant at regular intervals with *Concentrated Disinfectant Cleaner* (tested in accordance with the guideline list of the German Society for Hygiene and Microbiology and the German Society for Veterinary Medicine).
- 3.3 *Machine Cleaning:* In cases in which it is no longer possible to remove dirt adhering to the floor surface in the course of manual cleaning, it is recommendable to perform a machine cleaning operation with *PU Cleaner* in a dilution with water appropriate to the level of dirt present (e.g. 1:50 to 1:200) using a suitable automatic cleaning appliance (e.g. the *Premium F2*). This process is also suitable for intermediate cleaning of increased soiling on a rotational basis.

3. Stain Removal

Stains and rubber skid marks can be removed using *CC Elatex* universal stain remover and an absorbent cloth. Subsequently treat with clean water and dab dry. Clean up stains as soon as possible as some types of stain become fixed in the floor covering as they get older and can then be very difficult or even impossible to clear away completely.

These cleaning and maintenance instructions have been produced in consultation with the manufacturer of the floor covering. The quality, ecological compatibility and fields of application of the cleaning and care products mentioned have been confirmed by expertises from independent test institutes. **By passing on these Instructions for cleaning and care to its customer, the party responsible for installing new flooring has complied with DIN 18 365 regulations.**

If you have any further questions regarding the cleaning and care of resilient flooring or are interested in receiving cleaning instructions for textile floor coverings, please contact our Technical Applications Advisory Service. Our staff will be pleased to give you any assistance you require.

CC-Dr. Schutz GmbH



Holbeinstr. 17
53175 Bonn
Tel. (0228) 95352-0
www.dr-schutz.com