



Maintenance Guide for TAKIRON MT Sheet

September 2008



Hansaallee 191, D-40549 Düsseldorf, GERMANY
Tel.: +49 (0) 211 53067-220 Fax: +49 (0) 211 53067-280

www.cbc-de.com/toli

e-mail: toliflooring@cbc-de.com

CBC (Deutschland) GmbH is an ISO certified company

Precautions

- Close all working spaces to traffic while maintenance is in progress.
- Use care when working on the wet floor as cleaning products can make steps slippery during cleaning.
- Follow TAKIRON MT Sheet Maintenance Guide when using the cleaning solution.
- Proper matting system must be in place. Mats should be appropriate for soil load and weather conditions. Use mats with a non-staining backing.
- Floor protectors should be on all furniture legs.
- Keep heavy traffic and rolling loads off the newly installed TAKIRON MT Sheet for 48 hours.
- Cover TAKIRON MT Sheet with protective boards when moving furniture and other heavy loads to protect from scratches.
- Keep cleaning solution out of children's reach.
- Protect all cleaners from freezing.
- Allow the adhesive to fully set. *Do not flood-rinse TAKIRON MT Sheet for seven (7) days, instead damp mop the floor as needed for the first six (6) days.*

Initial Maintenance

Initial maintenance is critical to keep the original appearance and function of the TAKIRON MT.


Note: Adhesives used to install TAKIRON MT Sheet must have completely set before washing and/or finishing can take place.

1. Close all working spaces to traffic while maintenance is in progress. (Fig.1)



(Fig.1)

2. Sweep or vacuum the entire surface area to remove dirt and grit. (Fig.2)




(Fig.2)

3. Remove any adhesive residue.

4. Clean all surfaces with a mop soaked in clean water. Allow the area to dry completely. (Fig.3, 4)



(Fig.3)




(Fig.4)

Daily Maintenance

1. Close all working spaces to traffic while maintenance is in progress. (Fig.1)
2. Vacuum and mop all surfaces to remove dirt and grit. Mud, dirt or sand left on the flooring may cause stains and scratches on the floor surface. (Fig.2, 3)
3. Wash soiled flooring using the diluted solution of neutral detergent. Mop the surface with the cleaning

solution.

4. Pick up the solution with a wet-dry vacuum. (Fig.5)



(Fig.5)

5. Clean all surfaces with a mop soaked in clean water. Allow the area to dry completely. (Fig.4)

Periodic Maintenance

Periodic maintenance is recommended approximately every 2 months, depending on the use and contamination. More frequent maintenance is required if the flooring is severely stained.

1. Close all working spaces to traffic while maintenance is in progress. (Fig.1)
2. Vacuum and mop all surfaces to remove dirt and grit. (Fig.2, 3)
3. Wash heavily soiled flooring using the diluted solution of recommended cleaner or neutral detergent. Sweep the surface using a maintenance machine with a red pad. (Fig.6)



(Fig.6)

4. Pick up the solution with a wet-dry vacuum. (Fig.5)
5. Wipe the cleaned area three (3) times with a clean mop soaked in water.
6. Allow the area to dry completely. Keep off all traffic during drying. (Fig.4)